



OPUS LUBRICANTS PRODUCT DATA

BRAKE FLUID DOT 4

Description

A synthetic fluid for brake and clutch systems.

Performance Levels

The product shall fully meet the requirements of the latest issue of the US FMVSS 116 DOT 4, DOT 3, SAE J 1703, SAE J 1704 and ISO 4925 (Classes 3 & 4) Specifications. The product shall also meet the following requirements:

Test	Units	Method	Specification
Equilibrium Reflux Boiling Point	°C	FMVSS 116	230 Minimum
Wet Equilibrium Boiling Point	°C	FMVSS 116	155 Minimum
Kinematic Viscosity @ -40°C	cSt	ASTM D 445	1500 Max

Benefits

- Long service life.
- The DOT 4 specification gives excellent protection against brake failure giving a wet boiling point temperature greater than 155°C thereby giving a greater safety margin.
- Achieves maximum life from system components.
- Excellent compatibility with rubber parts and all metals.
- Highly stable.

Typical Data

Boiling Point °C:	266
Wet Boiling Point °C:	166

Revision Date: October 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk