



# OPUS LUBRICANTS PRODUCT DATA

## PLUS 10W/40 & 15W/40

### Description

**OPUS PLUS 10W/40 & 15W/40** are extremely high performance multigrade engine oils as indicated by the API classification CH-4/SJ.

They are eminently suitable for both turbo charged and naturally aspirated engines and are the perfect mixed fleet oils as they are designed to give top quality performance in both petrol and diesel engines.

### Performance Levels

- API: CH-4/SJ
- ACEA: E5
- MB: 228.1
- MTU Cat - 2
- MAN 3275
- Volvo VDS - 2

### Benefits

Mixed fleet advantages: rationalisation of grades: long drain capability: low temperature fluidity for easy starting: anti-wear, anti-oxidant and anti-corrosive properties.

### Typical Data

SAE		10W/40	15W/40
Specific Gravity	@ 15°C	0.869	0.871
Kinematic Viscosity	@ 100°C cSt	14.10	13.10
	@ 40°C cSt	97.60	94.10
Viscosity Index		147	137
Flash Point (COC °C)		210	210
Pour Point °C		-34	-27
TBN (mg KOH-gram)		11.0	11.0
Sulphated Ash (% weight)		1.4	1.4

Revision Date: July 2016

**Ferguson & Menzies Ltd**  
**312 Broomloan Road**  
**GLASGOW**  
**G51 2JW**

**Tel:** 0141 445 3555  
**Fax:** 0141 425 1079  
**E-Mail:** [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)  
**Web:** [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)