



OPUS LUBRICANTS PRODUCT DATA

CORROSIVE PREVENTATIVE ST 1.1

Description

Opus Corrosive Preventative ST 1.1 is a low odour solvent deposited dewatering corrosion preventive giving a light gelled oil film. Provides medium to short term protection on ferrous and aluminium alloy components and is particularly suited to inter-shop protection after machining operations. Will also act as a light lubricant for hinges/rollers and as penetrating oil.

Features & Benefits

- Good de-watering properties
- Oil film - no need to clean before assembly
- Contains finger print suppressant
- Good coverage per litre
- Can be removed easily if required
- Cost Effective
- Universal Application
- Low Odour

Application

Dip Tank: Using a wire basket submerge components for 30 seconds minimum. Lift from fluid allows draining and stacking to dry. Drain tank of excess water periodically.

Brush or Spray: Liberally apply to components and allow to dry. Use as a normal penetrating oil and apply directly to component. The oil residue will act as a good lubricant.

Covering Capacity: 58 sq.metres/litre.

Protection

Indoors -	minimum 6 months
Covered Outdoors -	minimum 3 months
Outdoors -	not recommended

Revision Date: April 2015

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk