OPUS LUBRICANTS PRODUCT DATA

SYNOPUS MAX FE 10W/40 LOW SAPS

Description

SYNOPUS MAX FE 10W/40 LOW SAPS is a very high spec heavy duty diesel engine oil that is designed to meet the necessary chemical limits required to maintain the efficiency of exhaust after-treatment devices, especially DPF's and SCR, EGR NOX reduction systems.

SYNOPUS MAX FE 10W/40 LOW SAPS provides the highest level of rationalisation in mixed fleets where a number of manufacturers, models and engines are being used. The Low Saps additive technology coupled with synthetic base oils also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals.

Applications

SYNOPUS MAX FE 10W/40 LOW SAPS is designed to allow fleet operators to run their new vehicles to maximum oil drain intervals. Its primary application is for the latest low emission Euro IV, Euro V and VI European trucks and buses, especially those requiring a Low SAPS lubricant.

Performance Levels

- API CJ4
- ACEA: E4, E6, E7, E9
- MB: 228.51 / MB:228.31
- VOLVO VDS 4
- MAN M3477/M3575/M3271-1
- RVI RXD / RLD-3/RLD-2
- SCANIA Low Ash
- MTU Type 3.1/2.1
- MACK EO-O Premium Plus
- Deutz DQC IV-10 LA
- Cummins CES 20081
- Caterpillar ECF-3
- Detroit Diesel 93K218
- JASO DH-2

Benefits

- Maximum oil drain intervals.
- The unique Low SAPS additive system keeps on working even in the toughest conditions.
- Efficient after-treatment systems. Maintains the efficiency of exhaust after-treatment systems ensuring continued compliance with emissions legislation.
- Engine protection. Designed to protect the latest European vehicles against all types of engine wear, deposit and soot build-up and bore-polishing. The unique formulation continues to protect under the most severe conditions, thus extending engine life.

Typical Data

SAE		**10W/40**
Specific Gravity	@ 15°C cSt	0.862
Kinematic Viscosity	@ 100°C cSt	14.50
	@ 40° C cSt	98.0
Viscosity Index		153
Total Base Number		12.0
Pour Point °C		-36
Flash Point °C		192
Sulphated Ash		<1.0

Revision Date: June 2017

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW
Tel: **0141 445 3555**
Fax: **0141 425 1079**
E-Mail: **info@fergusonmenzies.co.uk**
Web: **www.fergusonmenzies.co.uk**