

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/4

OPUS INDUSTRIAL GEAR OIL ISO 220

Revision 4
Revision date 2021-05-24

1.1. Product identifier

Product name OPUS INDUSTRIAL GEAR OIL ISO 220

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [SU17]

General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment; [PC24]

Lubricants, greases, release products;

1.3. Details of the supplier of the safety data sheet

Company Ferguson & Menzies Ltd

Address 312 Broomloan Road

Glasgow G51 2JW

Web www.fergusonmenzies.co.uk

Telephone 0141 445 3555

Email info@fergusonmenzies.co.uk

Email address of the competent person

info@fergusonmenzies.co.uk

1.4. Emergency telephone number

Emergency telephone number 0141-445-3555

09.00 - 17.00

SECTION 2: Hazards identification

2.2. Label elements

Risk phrases No Significant Hazard

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Alkyl amine		111-86-4	203-916-0		0 - 0.5%	Flam. Liq. 3: H226; Acute
						Tox. 3: H301; Acute Tox. 3:
						H311; Skin Corr. 1A: H314;
						Acute Tox. 4: H332; STOT
						SE 3: H335; Aquatic Acute 1:
						H400;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.	
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the	
	eyelids open. Seek medical attention if irritation or symptoms persist.	

OPUS INDUSTRIAL GEAR OIL ISO 220

Revision 4
Revision date 2021-05-24

4.1. Description of first aid meas	ures
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attentior if irritation or symptoms persist.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
	Use extinguishing media appropriate to the surrounding fire conditions.
5.2. Special hazards arising fron	n the substance or mixture
	Burning produces irritating, toxic and obnoxious fumes.
5.3. Advice for firefighters	
	Wear suitable respiratory equipment when necessary.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Ensure adequate ventilation of the working area.
6.2. Environmental precautions	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for co	ntainment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
6.4. Reference to other sections	
	See section 8 for further information.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handlin	g
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage,	including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
7.3. Specific end use(s)	
	See section 1.2 for further information.
SECTION 8: Exposure contr	ols/personal protection
3.1. Control parameters	
	Adopt best Manual Handling considerations when handling, carrying and dispensing.
3.2. Exposure controls	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	In case of splashing, wear:. Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
SECTION 9: Physical and ch	nemical properties

OPUS INDUSTRIAL GEAR OIL ISO 220

Revision 4 Revision date 2021-05-24

9.1. Information on basic physical and chemical properties

Appearance
Colour
Odour
Initial boiling point
Flash point
Flammability (solid, gas)
Relative density
Viscosity

Liquid
Brown
Characteristic
>200
230 °C
>200
0.894 @ 15°C
19.2 cSt @ 100°C

9.2. Other information

9.2. Other information		
Pour point	-15 °C	
SECTION 10: Stability and reactivity		
10.1. Reactivity		
	No data available.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous re	actions	
	Hazardous reactions will not occur under normal transport or storage conditions.	
10.4. Conditions to avoid		
	Heat, sparks and open flames.	
10.5. Incompatible materials		
	Strong oxidising agents.	
10.6. Hazardous decomposition	products	
	Do not breathe gas/fumes/vapour/spray.	
SECTION 11: Toxicological i	nformation	
11.1.4. Toxicological Information		
	No data available	
	No data is available on this product.	
SECTION 12: Ecological info	rmation	
12.1. Toxicity		
	No data available	
Further information		
	No data is available on this product.	
SECTION 13: Disposal cons	iderations	
General information		
	Dispose of in compliance with all local and national regulations.	
Disposal methods		
	Contact a licensed waste disposal company.	
Disposal of packaging		
	Dispose of in compliance with all local and national regulations.	
SECTION 14: Transport info	rmotion	

OPUS INDUSTRIAL GEAR OIL ISO 220

Revision 4
Revision date 2021-05-24

	The product is not classified as dangerous for carriage.	
14.2. UN proper shipping name		
	The product is not classified as dangerous for carriage.	
14.3. Transport hazard class(es)		
	The product is not classified as dangerous for carriage.	
14.4. Packing group		
	The product is not classified as dangerous for carriage.	
14.5. Environmental hazards		

14.6. Special precautions for user

The product is not classified as dangerous for carriage.

The product is not classified as dangerous for carriage.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

The product is not classified as dangerous for carriage.

Further information

14.1. UN number

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 12 - 12.1. Toxicity.
Text of Hazard Statements in Section 3	Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Acute Tox. 4: H332 - Harmful if inhaled. STOT SE 3: H335 - May cause respiratory irritation. Aquatic Acute 1: H400 - Very toxic to aquatic life.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and

combination with any other materials or in any other process.