

OPUS LUBRICANTS PRODUCT DATA

BIO HYDRAULIC ISO 46

Description

BIO Hydraulic 46 is a biodegradable high VI hydraulic fluid, blended from natural vegetable oils. BIO Hydraulic 46 incorporates the latest advances in modern additive technology, which ensures good oxidation stability, good anti-corrosion and excellent anti-wear characteristics. BIO Hydraulic 46 is non-scorch, non-toxic and ecologically more friendly to the environment.

Applications

BIO Hydraulic 46 should be used in all hydraulic systems where leakage may contaminate the soil, resulting in pollution of our natural waterways, i.e. in forestry and agricultural machinery, golf courses and earthmoving equipment. Because of its excellent low pour point (-26°C) and its high viscosity index stability (maximum operating temperature of +120°C).

BIO Hydraulic 46 will ensure excellent lubrication and all year-round protection.

Oil change intervals must be in line with manufacturers' instructions. When changing from mineral oil to biodegradable fluids, systems must be drained completely, as contamination from mineral oil would reduce biodegradability.

Benefits

- Non-scorch
- Non-toxic
- 98% biodegradability
- Anti-wear properties
- Anti-corrosion characteristics
- All year-round protection

Technical Data

Specific Gravity	@ 15.5 °C:	0.925
Kinematic Viscosity	@ 100 °C cSt:	8.5
	@ 40 °C cSt :	43.0
Viscosity Index:		210
Pour Point °C (ASTM D97):		-26
Flash Point °C:		330
Oxidation (mins):		200
Cu Corrosion (ASTM D130):		1A
Biodegradability:		>98%
Phytotoxicy:		Non phytotoxic
WGK Classification:		0

Revision Date: October 2016

Ferguson & Menzies Ltd312 Broomloan RoadGLASGOWG51 2JWTel:0141 445 3555Fax:0141 425 1079E-Mail:info@fergusonmenzies.co.ukWeb:www.fergusonmenzies.co.uk