



OPUS LUBRICANTS PRODUCT DATA

BIO HYDRAULIC ISO 68

Description

Opus Bio Hydraulic 68 is a biodegradable high VI hydraulic fluid, blended from natural vegetable oils. Opus Bio Hydraulic 68 incorporates the latest advances in modern additive technology, which ensures good oxidation stability, good anti-corrosion and excellent anti-wear characteristics. Opus Bio Hydraulic 68 is non-scorch, non-toxic and ecologically friendlier to the environment.

Applications

Opus Bio Hydraulic 68 should be used in all hydraulic systems where leakage may contaminate the soil, resulting in pollution of our natural waterways, i.e. in forestry and agricultural machinery, golf courses and earthmoving equipment. Because of its excellent low pour point (-26°C) and its high viscosity index stability (maximum operating temperature of +120°C). Opus Bio Hydraulic 68 will ensure excellent lubrication and all year-round protection. Oil change intervals must be in line with manufacturers' instructions. When changing from mineral oil to biodegradable fluids, systems must be drained completely, as contamination from mineral oil would reduce biodegradability.

Benefits

- Non-scorch
- Non-toxic
- 98% biodegradability
- Anti-wear properties
- Anti-corrosion characteristics
- All year-round protection

Technical Data

Specific Gravity	@ 15.5 °C:	0.926
Kinematic Viscosity	@ 100 °C cSt:	12.6
	@ 40 °C cSt :	68
Viscosity Index:		187
Pour Point °C (ASTM D97):		-23
Flash Point °C:		220
Oxidation (mins):		200
Cu Corrosion (ASTM D130):		1A
Biodegradability:		>98%
Phototoxic:		Non phototoxic
WGK Classification:		0

Revision Date: October 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk