



# OPUS LUBRICANTS PRODUCT DATA

## CHAINSAW OIL 46T; 68T; 100T; 150T; 220T

### Description

**Opus Chainsaw Oil T** is speciality oil formulated for the lubrication of all types of chainsaw cutter bars preventing damage or jam. It is enriched with special additives along with added extra tackiness to ensure excellent adhesion of the oil to the chain.

### Benefits

- Anti wear protection
- Non fling additive
- Protects chains against rusting and corrosion.

### Typical Data

| ISO GRADE            |             | 46T   | 68T   | 100T  | 150T  | 220T  |
|----------------------|-------------|-------|-------|-------|-------|-------|
| Specific Gravity     | @ 15°C      | 0.864 | 0.874 | 0.882 | 0.886 | 0.892 |
| Kinematic Viscosity  | @ 40°C cSt  | 44.0  | 68.00 | 100   | 150   | 220   |
|                      | @ 100°C cSt | 6.8   | 8.90  | 11.2  | 14.4  | 19.4  |
| Pour Point (°C)      |             | -24   | -12   | -12   | -11   | -10   |
| Flash Point COC (°C) |             | 220   | 220   | 240   | 240   | 240   |

Revision Date: September 2016

**Ferguson & Menzies Ltd**  
312 Broomloan Road  
GLASGOW  
G51 2JW

Tel: 0141 445 3555  
Fax: 0141 425 1079  
E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)  
Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)