

OPUS LUBRICANTS PRODUCT DATA

COMPRESSOR OIL

Description

OPUS COMPRESSOR OILS are a range of high performance oils manufactured from high quality mineral base oils and quality additives suitable for most piston and rotary screw compressors.

Performance Levels

DIN: 51506 VD-L

Service life of up to 4000 hours in reciprocating compressors.

Benefits

- Good oxidation resistance and rust protection
- High viscosity index
- High spontaneous ignition point
- Reduced risk of fires or explosion
- OPUS compressor oils frequently allow longer intervals between oil changes.

Typical Data

ISO GRADE		32	46	68	100
Specific Gravity Kinematic Viscosity	@ 15°C @ 100°C cSt	0.854 5.4	0.864 8.2	0.875 10.5	0.884 13.9
Kinematic Viscosity Viscosity Index	@ 40°C cSt	32.0 102	46.0 105	68.0 104	100.0 104
Pour Point (°C)		-14	-14	-13	-12
Flash Point COC (°C)		215	216	220	247

Revision Date: April 2017

Ferguson & Menzies Ltd 312 Broomloan Road GLASGOW G51 2JW

Tel: 0141 445 3555 Fax: 0141 425 1079

E-Mail: <u>info@fergusonmenzies.co.uk</u>
Web: <u>www.fergusonmenzies.co.uk</u>