



OPUS LUBRICANTS PRODUCT DATA

D ENGINE OIL 10W/40; 15W/40; 20W/50

Description

Adaptable high quality multigrade oil manufactured from quality solvent refined base oils and incorporating the most up to date detergent and dispersant additives. Designed for all petrol engines and most diesels, whether turbo charged or naturally aspirated.

Performance Levels

- API: CE/SH
- ACEA E1 Performance
- MIL-L-2104D
- MB 228.1 Blanket
- MIL-L-46152C
- CCMC: D4 G2

Benefits

- Excellent all round performance
- Meets the latest CCMC 'shear stability' requirements
- Economic mixed fleet applications.

Typical Data

SAE		10W/40	15W/40	20W/50
Specific Gravity	@ 15° C	0.882	0.882	0.891
Kinematic Viscosity	@ 100 °C cSt	14.5	14.5	18
Pour Point °C		-27	-27	-25
Flash Point °C		225	225	>200
TBN (mg KOH/gram)		10	10	10
Sulphated Ash (% weight)		1.5	1.5	1.5

Revision Date: August 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk