



OPUS LUBRICANTS PRODUCT DATA

FAME A.T.F. DEXRON III

Description

OPUS DEXRON III is an automatic transmission fluid blended from highly refined mineral and group 3 base oils and a high performance additive package. It is designed to meet the performance requirements of General Motors Dexron® IID specification.

Applications

Recommended for use in all applications where Dexron® IID is specified, including, automatic transmissions, powershift transmissions, torque converters, power steering units, fluid drives, hydraulic systems, brake boosters, transfer boxes, PTO's, hydrostatic drives, etc.

Performance Levels

- DIII-G
- Ford Mercon (M2C –185A)
- Allison C4
- Mercedes-Benz 236.9
- Volvo S6-66
- PSF Applications

Benefits

- A universal ATF with the frictional characteristics giving smooth and perfect gear changes for most automatic transmissions in all climates.
- High VI and low pour point.
- Highly resistant to oxidation, wear and corrosion.
- Excellent protection for all conventional seals.

Typical Data

Appearance		Red
Specific gravity	@ 15°C:	0.860
Kinematic Viscosity	@ 100°C cSt:	7.2
	@ 40°C cSt:	33.5
Viscosity Index:		187
Pour Point °C:		-30
Flash Point °C:		202

Revision Date: June 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW, G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk