



OPUS LUBRICANTS PRODUCT DATA

INDUSTRIAL OILS

Description

OPUS INDUSTRIAL OILS are a range of straight oils for a variety of applications according to the viscosity. The choice of grade depends upon the speed and load of the machinery. OPUS Industrial ISO 22 can also be used as quenching oil.

These products are produced from high quality paraffinic base stocks which are solvent refined.

Benefits

- Natural resistance to the formation of deposits at high temperatures.
- Low pour point gives adequate lubrication at low temperatures.

Typical Data

ISO GRADE		22	32	46	68
Specific Gravity	@ 15°C	0.865	0.870	0.875	0.879
Kinematic Viscosity	@ 40°C cSt	21.0	31.0	46.0	69.0
Viscosity Index		100	102	101	100
Pour Point (°C)		-12	-12	-12	-12
Flash Point COC (°C)		195	205	216	216

ISO GRADE		100	150	220	320	460
Specific Gravity	@ 15°C	0.885	0.889	0.892	0.900	0.905
Kinematic Viscosity	@ 40°C cSt	96.0	147.0	218.0	312.0	459.0
Viscosity Index		99	99	98	98	97
Pour Point (°C)		-10	-10	-9	-9	-9
Flash Point COC (°C)		216	226	226	226	260

Revision Date: October 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk