



OPUS LUBRICANTS PRODUCT DATA

PLUS 10W/40 & 15W/40

Description

OPUS PLUS 10W/40 & 15W/40 are extremely high performance multigrade engine oils as indicated by the API classification CH-4/SJ.

They are eminently suitable for both turbo charged and naturally aspirated engines and are the perfect mixed fleet oils as they are designed to give top quality performance in both petrol and diesel engines.

Performance Levels

- API: CH-4/SJ
- ACEA: E5
- MB: 228.1
- Caterpillar: ECF-1a, ECF-2
- MTU Type 2
- MAN 3275
- Volvo VDS - 2

Benefits

Mixed fleet advantages: rationalisation of grades: long drain capability: low temperature fluidity for easy starting: anti-wear, anti-oxidant and anti-corrosive properties.

Typical Data

SAE		10W/40	15W/40
Specific Gravity	@ 15°C	0.869	0.874
Kinematic Viscosity	@ 100°C cSt	14.10	13.10
	@ 40°C cSt	97.60	94.10
Viscosity Index		147	137
Flash Point (COC °C)		210	210
Pour Point °C		-34	-27
TBN (mg KOH-gram)		11.0	11.0
Sulphated Ash (% weight)		1.4	1.4

Revision Date: October 2018 (AB)

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk