



OPUS LUBRICANTS PRODUCT DATA

PLUS SAE 30; SAE 40

Description

OPUS PLUS SAE 30 and SAE 40 are extremely high-performance monograde engine oil as indicated by the API classification of CI-4/SJ. They are manufactured from highly refined base oils quality additives producing high quality petrol and diesel engine oils.

They are eminently suitable for both turbo charged and naturally aspirated engines and are the perfect mixed fleet engine oils designed to give top performance in both petrol and diesel engines.

Performance Levels

- API: CI-4
- ACEA: E7
- Allison: C4
- CAT ECF-2
- Volvo: VDS-3
- MAN: 3275
- MB: 228.3
- MTU 2.0
- Cummins CES 20078
- Mack EO-N

Benefits

Mixed fleet advantages; rationalisation of grades; long drain capability; low temperature fluidity for easy starting; anti-wear, antioxidant, and anti-corrosive properties

Typical Data

| SAE | | 30 | 40 |
|----------------------|-------------|-------|-------|
| Specific Gravity | @ 15°C cSt | 0.886 | 0.889 |
| Kinematic Viscosity | @ 100°C cSt | 11.15 | 14.54 |
| | @ 40°C cSt | 97.13 | 143.0 |
| Viscosity Index | | 100 | 99 |
| Pour Point °C | | -19 | -18 |
| Flash Point (COC °C) | | 210 | 212 |
| TBN (mg KOH/gram) | | 11.00 | 11.00 |

Revision Date: September 2016