

OPUS LUBRICANTS PRODUCT DATA

SYNOPUS NOVA 5W/30 LOW SAPS

Description

SYNOPUS NOVA 5W/30 Low SAPS oil is a fully synthetic multigrade engine oil formulated to meet the performance and fuel efficiency requirements of engines requiring low viscosity oils for petrol and diesel engine applications.

SYNOPUS NOVA 5W/30 Low SAPS is compatible with engines fitted with diesel particulate filters (DPFs) and 3 way catalysts (TWC)

Applications

SYNOPUS NOVA 5W/30 Low SAPS is recommended for use in the latest petrol and passenger car diesel engines including turbo and supercharged versions requiring a low saps oil.

Performance Levels

- ACEA C4
- Renault RN 0720
- MB 229.51, 226.51

Benefits

- Maximum oil drain intervals.
- Increased engine efficiency, output and fuel economy.
- Low levels of volatility.
- Excellent cold starting, reduced noise and wear.
- Excellent thermal stability and improved engine cleanliness.

Typical Data

SAE		5W/30
Specific Gravity	@ 15°C cSt	0.852
Kinematic Viscosity	@ 100°C cSt	11.4
	@ 40° C cSt	68
Viscosity Index		164
CCS –25°C		4500
Total Base Number		7.0
Pour Point °C		-42
Flash Point °C		210
Sulphated Ash		< 0.5



Revision Date: May 2019

Ferguson & Menzies Ltd 312 Broomloan Road GLASGOW G51 2JW

Tel: 0141 445 3555 Fax: 0141 425 1079

E-Mail: <u>info@fergusonmenzies.co.uk</u>
Web: www.fergusonmenzies.co.uk