

## SAFETY DATA SHEET according to 1907/2006/EC, Article 31

Page 1/5

# OPUS GEAR OIL 80W/90 GL5

 Revision
 1

 Revision date
 2015-10-15

SECTION 1: Identification	n of the subs	tance/mix	ture and of	the company/und	ertaking		<b>date</b> 2015-10
1.1. Product identifier							
Product name	OPUS C	GEAR OIL 8	30W/90 GL5				
I.2. Relevant identified uses	of the substa	nce or mixt	ure and use	s advised against			
Product Use	General	manufactu		chinery, equipment		arations at industrial sit other transport equipr	
1.3. Details of the supplier of	the safety da	ita sheet					
Company	Ferguso	on & Menzie	es Ltd				
Address		omloan Ro v G51 2JW	ad				
Web	www.fer	gusonmen	zies.co.uk				
Telephone	0141-44	5 3555					
Fax	0141-42	25 1079					
Email	info@fe	rgusonmen	zies.co.uk				
Email address of the competent person	info@fe	rgusonmen	zies.co.uk				
1.4. Emergency telephone nu	umber						
Emergency telephone numb	<b>er</b> 0141-44	5-3555					
	09.00 -	17.00					
SECTION 2: Hazards ide	ntification						
2.1. Classification of the subs	stance or mix	ture					
Main hazards	No Sigr	nificant Haz	ard				
2.2. Label elements	-						
Risk phrases	No Sigr	nificant Haz	ard				
SECTION 3: Composition	/information	on ingred	lients				
3.2. Mixtures							
67/548/EEC / 1999/45/EC							
Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc. (%w/w)	Classification	M-factor.
SULPHURISED ISOBUTYLENE			270-943-2		<u> </u>	R52/53	
Long chain alkenyl amine			204-015-5		0 - 0.5%	C; R34 Xn; R22-48/22 Xi; R37 N; R50	



## OPUS GEAR OIL 80W/90 GL5

#### 3.2. Mixtures

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
ong chain alkenyl amine			204-015-5		0 - 0.5%	6 Acute Tox. 4: H302; Skin	
						Corr. 1B: H314; Eye Dam. 1:	
						H318; STOT SE 3: H335;	
						STOT RE 2: H373; Aquatic	
						Acute 1: H400;	

#### 4.1. Description of first aid measures

Inhalation	May cause irritation to mucous membranes. Move the exposed person to fresh air.		
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.		
Skin contact	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.		
Ingestion	May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.		

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Use extinguishing media appropriate to the surrounding fire conditions.

#### 5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

### 5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area.

### 6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

## 6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

### 6.4. Reference to other sections

See section 8 for further information.

## SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled
containers.

## 7.3. Specific end use(s)

See section 1.2 for further information.

#### SECTION 8: Exposure controls/personal protection



## OPUS GEAR OIL 80W/90 GL5

Revision 1 Revision date 2015-10-15

### 8.1. Control parameters

	Adopt best Manual Handling considerations when handling, carrying and dispensing.
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear protective clothing.
Eye / face protection	In case of splashing, wear:. Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).

### SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Appearance Colour	Liquid
Colour	Brown
Odour	Characteristic
Flash point	172 °C
Viscosity	15.8 cSt @ 100°C

### 9.2. Other information

Specific gravity	0.893 g/cm³
Pour point	-33 °C

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

	No data available.			
10.2. Chemical stability				
	Stable under normal conditions.			
10.3. Possibility of hazardous re	actions			
	Hazardous reactions will not occur under normal transport or storage conditions.			
10.4. Conditions to avoid				
	Heat, sparks and open flames.			
10.5. Incompatible materials				
	Strong oxidising agents.			
10.6. Hazardous decomposition products				
	Do not breathe gas/fumes/vapour/spray.			
SECTION 11: Toxicological information				
11.1.4. Toxicological Information				

	No data is available on this product.		
	No data available		
	Ne dete evelleble		

## SECTION 12: Ecological information

## 12.1. Toxicity

No data available

## Further information

No data is available on this product.



1

Revision

Revision date 2015-10-15

# OPUS GEAR OIL 80W/90 GL5

SECTION 13: Disposal considerations			
General information			
	Dispose of in compliance with all local and national regulations.		
Disposal methods			
	Contact a licensed waste disposal company.		
Disposal of packaging			
	Dispose of in compliance with all local and national regulations.		
SECTION 14: Transport info	rmation		
14.1. UN number	matori		
	The modulatic net classified as descentions		
	The product is not classified as dangerous for carriage.		
14.2. UN proper shipping name			
	The product is not classified as dangerous for carriage.		
14.3. Transport hazard class(es)			
	The product is not classified as dangerous for carriage.		
14.4. Packing group			
	The product is not classified as dangerous for carriage.		
14.5. Environmental hazards			
	The product is not classified as dangerous for carriage.		
14.6. Special precautions for use	۶ſ		
	The product is not classified as dangerous for carriage.		
14.7. Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code		
	The product is not classified as dangerous for carriage.		
Further information			
	The product is not classified as dangerous for carriage.		
SECTION 15: Regulatory inf	ormation		
	mental regulations/legislation specific for the substance or mixture		
	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No		
	1907/2006 of the European Parliament and of the Council on the Registration, Evaluation,		
	Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency,		
	amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and		
	Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.		
SECTION 16: Other informat	tion		
Other information			
Revision	This document differs from the previous version in the following areas:.		
	9 - 9.1. Information on basic physical and chemical properties (Flash point).		
	9 - 9.1. Information on basic physical and chemical properties (Viscosity).		
	9 - 9.2. Other information (Specific gravity). 9 - 9.2. Other information (Pour point).		
	12 - 12.1. Toxicity.		
Text of risk phrases in Section	R22 - Harmful if swallowed.		
3	R34 - Causes burns.		
	R37 - Irritating to respiratory system.		
	R48/22 - Harmful: danger of serious damage to health by prolonged exposure if swallowed. R50 - Very toxic to aquatic organisms.		



# OPUS GEAR OIL 80W/90 GL5

Other information	
	R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Text of Hazard Statements in	Acute Tox. 4: H302 - Harmful if swallowed.
Section 3	Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
	Eye Dam. 1: H318 - Causes serious eye damage.
	STOT SE 3: H335 - May cause respiratory irritation.
	STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .
	Aquatic Acute 1: H400 - Very toxic to aquatic life.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in

combination with any other materials or in any other process.

