



OPUS LUBRICANTS PRODUCT DATA

HYDRAULIC HVI-ZF OILS (Ashless Grades)

Description

A high quality and fully inhibited range of High Viscosity Index and Zinc Free Hydraulic Oils, manufactured from a blend of mineral oils, including a high shear polymer and a multipurpose ashless hydraulic oil additive covering a wide range of viscosities and suitable for hydraulic systems where the use of zinc free additives is specified, including silver bearings.

Performance Levels

Opus HVI-ZF Hydraulic Oils are approved to meet the following specifications.

- Denison: HF-1, HF-2, HF-O
- Vickers: 1-286-S3, M-2950-S
- Cincinnati Milacron P-68, P-69, P-70
- DIN 51524, Part
- Bosch Rexroth 07075, 90220

Benefits

- Excellent oxidation resistance and rust protection
- Low pour points
- Anti-foam characteristics.

Typical Data

ISO GRADE		32	46	68	100
Specific Gravity	@ 15°C	0.864	0.868	0.876	0.880
Kinematic Viscosity	@ 100°C cSt	6.30	8.10	10.70	14.40
	@ 40°C cSt	32.0	46.0	68.0	100.0
Viscosity Index		151	150	147	148
Pour Point (°C)		-36	-36	-34	-32
Flash Point (°C)		205	216	216	247
Cleanliness Test:		NAS. 7			
FZG Gear Test, pass load:		12	12	12	12
Rust Test:		Pass	Pass	Pass	Pass
Cleanliness Test:		NAS 7	NAS 7	NAS 7	NAS 7

Revision Date: April 2019

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk