



OPUS LUBRICANTS PRODUCT DATA

FAME XS 10W/40

Description

OPUS FAME XS 10W/40 is an extremely high performance long life diesel engine oil, based on synthetic technology meeting the requirements for Scania and the latest Euro 6 engines, also suitable for most Euro 4 & Euro 5 engines without Diesel Particulate Filters. The API & ACEA classification allows fleet operators to run new vehicles to maximum drain periods.

Performance Levels

- API: CI-4
- ACEA: E4, E7
- MAN: M3277
- Volvo: VDS-3
- Mercedes-Benz: 228.5
- Renault: RLD-2
- Scania: LDF-2/LDF-3
- DEUTZ DQC IV – 10
- Mack EO-N
- MTU Type 3
- Caterpillar ECF-2
- Jaso DH-1
- Cummins CES 20078

Benefits

- Extended intervals between oil changes.
- Improved performance under all conditions.
- Increased engine protection and low volatility.

Typical Data

SAE		10W/40
Specific Gravity	@ 15 °C	0.866
Kinematic Viscosity	@ 100°C cSt	13.6
	@ 40°C cSt	89.9
Viscosity Index		154
Pour Point °C		-42
Flash Point COC (°C)		240
TBN (mg KOH/gram)		16

Revision Date: January 2020

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk