

OPUS CONSTRUCTION PRODUCT DATA

EASYSTRIKE QS202

Description

Opus Easystrike QS202 is manufactured from high quality synthetic lubricants and release additives dispersed in a refined hydrocarbon oil carrier, yielding a low viscosity fluid to BCA Category 2. The Product is designed for repetition casting of semi-dry and semi-wet concrete mixes. It is particularly useful for alloy Moulds for the Production of more intricate Castings. The Product may also be used as a Category 2 Mould Release Agent for wet cast Production.

Advantages

- Excellent lubricity and Release Properties with semi-dry Concrete mixes, even on alloy Moulds.
- Promotes outstanding cleanliness of Mould surfaces and is essentially non-staining to the Cast Concrete.
- Good rust inhibiting properties when used on steel Moulds.
- Product has high flash point, minimizing potential fire hazards.
- Low viscosity Product ensures ease of application even at low temperatures.

Physical Properties

Appearance	Pale Yellow Liquid
Viscosity at 25°C	2 cst
Flash Point	70°C (PMCC)
Density @ 15°C	0.802
Odour	Mild
Freezing Point	Below 25°C

Applications

Opus Easystrike QS202 is supplied ready for use and should be applied undiluted, by low pressure spray or brush ensuring that a liberal coating is achieved for semi-dry or semi wet castings. When used for wet casting apply sparingly ensuring a thin even coverage is achieved.

Limitations

Care should be taken when using QS202 on certain specialized plastics and rubber liners which could lead to the degradation of the Mould



Health and safety

The Product is manufacture form highly refined raw materials and does not contain any components defined as hazardous. Please refer to the material Health and Safety Data sheet for additional

information. Combustible Release Agents of this type should be applied in well ventilated areas and kept away from flames and other ignition sources.

Packaging

Opus Easystrike QS202 is supplied 1000 litre IBC's, 205 litre drums & 20 litre containers.

Revision Date: June 2016

Ferguson & Menzies Ltd 312 Broomloan Road GLASGOW G51 2JW

Tel: 0141 445 3555 Fax: 0141 425 1079

E-Mail: <u>info@fergusonmenzies.co.uk</u>
Web: <u>www.fergusonmenzies.co.uk</u>