

OPUS LUBRICANTS PRODUCT DATA

SLIDEWAY OIL 68T

Description

OPUS SLIDEWAY OIL 68T has been formulated from high quality mineral oils, additives and incorporate a tackifier to ensure that the oil adheres to the moving parts. The additives provide outstanding resistance to oxidation, corrosion and wear and eliminate stick slip and judder that sometimes occurs in mechanically and hydraulically operated machine tools.

Benefits

- Excellent slideway oil with good lubricity under low speed or high load conditions.
- High film strength.
- Excellent pressure, anti wear and anti rust properties.
- Product has an extra tackiness

Performance Levels

- Cincinnati Milacron P-47/P-50
- Siderurgie Francaise FT 172
- Staticinemeter SF/BP

Typical Data

ISO GRADE		68T
Specific Gravity	@ 15°C cSt	0.883
Kinematic Viscosity	@ 40°C cSt	64.48
Pour Point (°C)		-12
Flash Point (°C)		245

Revision Date: June 2016

Ferguson & Menzies Ltd		
312 Broomloan Road		
GLASGOW		
G51 2JW		
Tel:	0141 445 3555	
Fax:	0141 425 1079	
E-Mail:	info@fergusonmenzies.co.uk	
Web:	www.fergusonmenzies.co.uk	