



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS MAX FE 10W/40 LOW SAPS

Description

SYNOPSIS MAX FE 10W/40 LOW SAPS is a very high spec heavy duty diesel engine oil that is designed to meet the necessary chemical limits required to maintain the efficiency of exhaust after-treatment devices, especially DPF's and SCR, EGR NOX reduction systems.

SYNOPSIS MAX FE 10W/40 LOW SAPS provides the highest level of rationalisation in mixed fleets where a number of manufacturers, models and engines are being used. The Low Saps additive technology coupled with synthetic base oils also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals.

Applications

SYNOPSIS MAX FE 10W/40 LOW SAPS is designed to allow fleet operators to run their new vehicles to maximum oil drain intervals. Its primary application is for the latest low emission Euro V and VI European trucks and buses, especially those requiring a Low SAPS lubricant.

Performance Levels

- ACEA: E4/E7/E8/E11-22
- API: CK-4
- MB: 228.31 / 228.51 228.52
- MAN M3775 / M3477 / M3271-1
- MTU Type 3.1 / Type 2.1
- Deutz DQC IV-18 LA
- VOLVO VDS 4.5
- RLD-4 / RLD-3
- SCANIA LA
- Mack EOS – 4.5
- Caterpillar ECF-3
- Cummins CES 20086 / CES 20081
- DH-2-17
- Detroit Diesel 93K222

Benefits

- Maximum oil drain intervals.
- The unique Low SAPS additive system keeps on working even in the toughest conditions.
- Efficient after-treatment systems. Maintains the efficiency of exhaust after-treatment systems ensuring continued compliance with emissions legislation.
- Engine protection. Designed to protect the latest European vehicles against all types of engine wear, deposit and soot build-up and bore-polishing. The unique formulation continues to protect under the most severe conditions, thus extending engine life.



Typical Data

SAE		10W/40
Specific Gravity	@ 15°C cSt	0.856
Kinematic Viscosity	@ 100°C cSt	14.75
	@ 40° C cSt	99.0
Viscosity Index		153
Total Base Number		12.0
Pour Point °C		-36
Flash Point °C		192
Sulphated Ash		<1.0

Revision Date: March 2023

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW
Tel: 0141 445 3555 E-Mail: info@fergusonmenzies.co.uk Web: www.fergusonmenzies.co.uk