

OPUS LUBRICANTS PRODUCT DATA

SYNOPUS NOVA C4 5W/30 LOW SAPS

Description

Synopus Nova C4 5W/30 Low SAPS (Sulphated Ash, Phosphorus, Sulphur) fully synthetic based multigrade engine oil is formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils for petrol and diesel engine applications.

Synopus Nova C4 5W/30 has been developed to protect sensitive exhaust after-treatment devices, particularly those fitted with diesel particulate filters (DPF's) and 3-way catalysts (TWC)

The additive technology coupled with synthetic base fluids also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals. It is a long-life engine oil which meets the following requirements:

Performance Levels

- ACEA C4
- Renault RN 0720
- MB 226.51

Benefits

- Low SAPS technology, ensuring protection of exhaust after-treatment systems
- Increased engine efficiency, output and improved fuel economy
- Ensures lubricant performance over extended drain intervals
- Improved engine wear protection
- Excellent long term anti-wear and oxidation stability
- Excellent high and low temperature performance



Typical Data

SAE		5W/30
Specific Gravity Kinematic Viscosity	@ 15°C cSt@ 100°C cSt@ 40°C cSt	0.850 10.3 59.0
Viscosity Index TBN, mg/KOH/g Phosphorous, %Wt Pour Point °C Flash Point °C		164 7.90 0.05 -42 210
Sulphated Ash		<0.5

Revision Date: May 2019

Ferguson & Menzies Ltd 312 Broomloan Road GLASGOW G51 2JW

Tel: 0141 445 3555 Fax: 0141 425 1079

E-Mail: <u>info@fergusonmenzies.co.uk</u>
Web: www.fergusonmenzies.co.uk