



SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

OPUS EASYCURE R75AL

Revision 0

Revision date 2017-09-21

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name OPUS EASYCURE R75AL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites;

1.3. Details of the supplier of the safety data sheet

Company Ferguson & Menzies Ltd
Address 312 Broomloan Road
Glasgow G51 2JW
Web www.fergusonmenzies.co.uk
Telephone 0141-445 3555
Fax 0141-425 1079
Email info@fergusonmenzies.co.uk
Email address of the competent person info@fergusonmenzies.co.uk

1.4. Emergency telephone number

Emergency telephone number 0141-445-3555
09.00 - 17.00

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC
Xn; R65 Xi; R37 N; R51/53 R10-66-67
Symbols: Xn: Harmful. N: Dangerous for the environment.

Main hazards
Flammable. Irritating to respiratory system. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.1.2. Classification - EC 1272/2008
Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;

2.2. Label elements

Hazard pictograms



Signal Word

Danger

Hazard Statement

Flam. Liq. 3: H226 - Flammable liquid and vapour.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .

OPUS EASYCURE R75AL

Revision 0

Revision date 2017-09-21

2.2. Label elements

Precautionary Statement: Prevention	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
Precautionary Statement: Response	P241 - Use explosion-proof electrical/ventilating/lighting// equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static discharge.
	P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 - Wash thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Storage	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ .
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
	P314 - Get medical advice/attention if you feel unwell.
Precautionary Statement: Disposal	P331 - Do NOT induce vomiting.
	P370+P378 - In case of fire: Use to extinguish.
	P391 - Collect spillage.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
	P403+P235 - Store in a well-ventilated place. Keep cool.
	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons, C9, Aromatics			918-668-5		20 - 30%	Xn; R65 Xi; R37 N; R51/53 R10-66-67	
WHITE SPIRIT		64742-88-7	265-191-7		60 - 70%	Xn; R65 N; R51/53 R10-66-67	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Hydrocarbons, C9, Aromatics			918-668-5		20 - 30%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;	
WHITE SPIRIT		64742-88-7	265-191-7		60 - 70%	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; STOT RE 1: H372; Aquatic Chronic 2: H411;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention.
Eye contact	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

OPUS EASYCURE R75AL

Revision 0

Revision date 2017-09-21

4.1. Description of first aid measures

Skin contact	May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam.
--	---

5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

6.4. Reference to other sections

	See section 8 for further information.
--	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

7.3. Specific end use(s)

	See section 1.2 for further information.
--	--

SECTION 8: Exposure controls/personal protection

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

OPUS EASYCURE R75AL

Revision 0
Revision date 2017-09-21

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Silver
Odour	Characteristic
Freezing Point	-15 °C
Flash point	40 °C
Relative density	0.86 @ 15°C

SECTION 10: Stability and reactivity

10.1. Reactivity

	No data is available on this product.
--	---------------------------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Hazardous reactions will not occur under normal transport or storage conditions.
--	--

10.4. Conditions to avoid

	No data is available on this product.
--	---------------------------------------

10.5. Incompatible materials

	No data is available on this product.
--	---------------------------------------

10.6. Hazardous decomposition products

	Do not breathe gas/fumes/vapour/spray.
--	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Repeated or prolonged exposure	Irritating to respiratory system and skin.
--------------------------------	--

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

	Not readily biodegradable.
--	----------------------------

12.3. Bioaccumulative potential

	Bioaccumulation.
--	------------------

Further information

	Toxic to aquatic organisms.
--	-----------------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

Disposal methods

	Contact a licensed waste disposal company.
--	--

Disposal of packaging

OPUS EASYCURE R75AL

Revision 0

Revision date 2017-09-21

Disposal of packaging

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1268

14.2. UN proper shipping name

PETROLEUM DISTILLATES. N.O.S.

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

SECTION 16: Other information

OPUS EASYCURE R75AL

Revision 0

Revision date 2017-09-21

Other information

Text of risk phrases in Section 3	<p>R10 - Flammable</p> <p>R37 - Irritating to respiratory system.</p> <p>R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65 - Harmful: may cause lung damage if swallowed.</p> <p>R66 - Repeated exposure may cause skin dryness or cracking.</p> <p>R67 - Vapours may cause drowsiness and dizziness.</p>
Text of Hazard Statements in Section 3	<p>Flam. Liq. 3: H226 - Flammable liquid and vapour.</p> <p>Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.</p> <p>STOT SE 3: H335 - May cause respiratory irritation.</p> <p>STOT SE 3: H336 - May cause drowsiness or dizziness.</p> <p>Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.</p> <p>STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure .</p>

Further information

	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
--	---