



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS HT PLUS 5W/30

Description

SYNOPSIS HT-PLUS 5W/30 is a multifunctional Hydraulic/Transmission Oil (UTTO) for Tractor Transmissions and Plant engineered to meet the tough demands of heavy-duty, hydraulic-powered farm and commercial equipment. The Synthetic base stocks and additives effectively reduces wear, resists heat, protects against rust and extends fluid and equipment service life. Synopsis HT-Plus 5W/30 Hydraulic/Transmission Oil is recommended for extended oil drain intervals based on an oil analysis program.

Performance Levels

- John Deere: J20C & J20D
- Ford: M2C134D, M2C86B,C
- Case International:
MS1204,1206,1207,1209
- CNH MAT3526
- New Holland: NH420A, NH410B
- Massey Ferguson:
M1135,M1141,M1143,M1145
- Volvo WB 101, 97303
- ZF TE ML
03E/05F/06E/06F/06K/17E/21E
- Allison: C4
- Caterpillar: TO-2
- API: GL-4
- Denison: HF-0,HF-1,HF-2
- Sperry Vickers/Eaton: I-280-S &
M2950S

Benefits

- Excellent anti-squawk properties.
- Suitable for nearly all hydraulic, transmission and differential systems.
- Excellent thermal and oxidation stability.

Typical Data

SAE		5W/30
Specific Gravity	@ 15°C	0.855
Kinematic Viscosity	@ 100°C cSt	10.10
	@ 40°C cSt	55.40
Viscosity Index		171
Flash Point °C		228
Pour Point °C		-48
Cold-Crank Simulator -30°C		4695
Brookfield Viscosity @ -40°C		18795

March 2022