



# OPUS LUBRICANTS PRODUCT DATA

## OPTIMO NC4

### Description

**Opus Optimo NC4** has been developed for use on medium tensile steels and all non-ferrous metals in a wide range of machinery. Opus Optimo NC4 contains inactive sulphur EP and lubricity additives together with anti-mist and anti-oxidant packages.

The product is suitable for use as a lubricating oil where a viscosity grade of ISO 32 is required. It can be utilized in automatic lathes where cross leakage into gearboxes can occur.

### Benefits

- EP and lubricity additives.
- Anti-misting formulation.
- Light colour.
- Formulated on high quality mineral oil.
- Multipurpose Oil.
- Enhances component finish.
- Can be used as a lubricating oil in certain machinery.
- Medium – High viscosity Oil

### Typical Data

Colour:	Light Brown
Viscosity @ 40 °C:	32 mm <sup>2</sup> /s
Sulphur:	Yes - Inactive
Ester:	Yes
Specific Gravity:	0.88

### Operational Recommendations

Opus Optimo NC4 is designed to be used as supplied and is safe to use on most metals. Opus Optimo NC4 should always be stored indoors and protected from extremes of temperature.

Revision Date: November 2020

**Ferguson & Menzies Ltd**  
**312 Broomloan Road**  
**GLASGOW**  
**G51 2JW**

**Tel:** 0141 445 3555  
**E-Mail:** [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)  
**Web:** [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)