



OPUS LUBRICANTS PRODUCT DATA

FAME 5W/30

Description

FAME 5W/30 is a semi-synthetic multigrade engine oil manufactured using high quality additives and base oils for fuel efficiency and superior performance for petrol and diesel engines of modern passenger cars and light commercial vehicles.

The additive technology coupled with synthetic base fluids also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals.

Performance Levels

- ACEA: A1/B1
- API: SL/CF
- FORD WSS - M2C 913-B
- BMW LL-01
- OPEL – Pass
- ILSAC GF-2

Benefits

- Fuel economy, particularly when used in conjunction with Fame 75W/90 transmission oil.
- Meets NOACK volatility requirements of CCMC D4.
- High viscosity index at 160
- Excellent cold starting.

Technical Data

SAE		5W/30
Specific Gravity	@ 15°C (typical)	0.867
Kinematic Viscosity	@ 100°C cSt	11.25
	@ 40°C cSt	67.43
Viscosity Index		160
Pour Point °C		-45
Flash Point °C		215

Revision Date: September 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW
Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk