



OPUS LUBRICANTS PRODUCT DATA

SYNOPSIS MULTIVEHICLE CVT FLUID

Description

Synopsis Multivehicle CVT Fluid is a premium, high performance, fully synthetic fluid designed to meet the exacting specifications of Continuously Variable Transmissions found in many modern vehicles.

Application

Formulated to meet the wide range of CVT requirements from manufacturers such as **Honda, Mazda, Mitsubishi, Nissan, Toyota, Kia** and **Hyundai**, as well as many European OEM's using CVT transmissions, such as **VW / Audi** and **BMW / Mini**.

Benefits

- Outstanding anti-wear protection to extend transmission life.
- Exceptional anti-shudder capabilities to promote smooth power transmission.
- Offers enhanced shift quality even in extreme low temperature environments.
- Exceptional fluidity throughout the high-low temperature range.
- Formulated to maintain viscosity and film strength even during high temperature operation.
- Excellent oxidation and thermal resistance for longer component and fluid life.

Performance Profile

Suitable for use where the following specifications are required;

- **BMW/MINI** EZL799, EZL799A
- **MINI COOPER** ZF CVT V1
- **CHRYSLER/JEEP** NS-2, CVT+4
- **FORD** M2C 928-A (CFT 23)
- **FORD** M2C 933-A (CFT 30)
- **FIAT** CVT N.G.
- **GM** DEX CVT, CVTF I-Green2
- **HONDA** HMMF
- (without starting clutch)
- **HONDA** HCF-2, e:HEV, iMMD
- **HONDA** Ultra HEVF-Type 1
- **HYUNDAI/KIA** CVT-1
- **JATCO** CVT 8 Hybrid
- **MAZDA** JWS 3320
- **MERCEDES-BENZ** MB 236.20
- **MITSUBISHI** CVTF-J1, J4
- **MITSUBISHI** CVTF-J4+, ECO J4
- **MITSUBISHI** SPIII (CVT only)
- **NISSAN** NS-1, NS-2 / 2V, NS-3
- **PEUGEOT** PSA 9735EF
- **RENAULT** Elf Matic CVT
- **RENAULT** CVT CK/SK/FK
- **SUBARU** iCVT, iCVT-FG, ECVT
- **SUBARU** Lineartronic CVT / II
- **SUBARU** Lineartronic CVT 3
- **SUBARU** Lineartronic HT CVT
- **SUZUKI** CVTF TC
- **SUZUKI** NS-2
- **SUZUKI** CVT Green 1, 2
- **SUZUKI** CVT Green 1V
- **SUZUKI** CVTF TC, 3320, 4401
- **TOYOTA/LEXUS** CVTF TC, FE
- **TOYOTA** THS II / Prius
- **TOYOTA** THS 5th Gen
- **VAUXHALL/OPEL** 7-sp CVT
- **VAUXHALL/OPEL** 95529854
- **VOLVO** CVT 4959
- **VW/AUDI** TL 521 16
- **VW/AUDI** G 052 516
- **VW/AUDI** TL 521 80
- **VW/AUDI** G 052 180 A2
- **VW/AUDI** Multitronic
- **Not recommended for DCT transmissions**



Typical Properties

| | |
|------------------------------------|---------------|
| Appearance: | Yellow/amber |
| Specific Gravity @ 15.6°C: | 0.850 |
| Kinematic Viscosity @ 100°C (cSt): | 7.3 (typical) |
| Flash Point (closed cup) °C : | 186 |

Health & Safety

This product has been manufactured to the highest standards and when used for the purpose recommended is unlikely to present any significant health hazards. A Safety Data Sheet is available on request.

Revision Date: March 2023

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW
Tel: 0141 445 3555 E-Mail: info@fergusonmenzies.co.uk Web: www.fergusonmenzies.co.uk