



OPUS LUBRICANTS PRODUCT DATA

FAME AUTOMATIC TRANSMISSION FLUID 3 LL (LT71141)

Description

Opus Fame A.T.F. 3 LL is a semi-synthetic product blended from carefully selected highly refined special base oils and modern additive technology to guarantee that it fulfils the severest ATF “fill for life” requirements of international automatic transmission manufacturers.

Performance Levels

- Dexron IIIH
- MERCON V
- Allison C4
- Voith H55.6335.xx, MAN 339 Type V1
- ZF 14A/14B, MAN 339 Type Z1/Z2
- MB 236.9
- VOLVO 97341

Benefits

- Long drain performance for use in automatic transmissions and power steering units.
- High performance semi-synthetic based oil suitable for operation over a wide temperature range.
- Meets the severest ATF “fill for life” requirements of major international transmission manufacturers.

Typical Data

Specific gravity	@ 15°C, kg/m ³ :	0.853
Kinematic Viscosity	@ 40°C, mm ² /sec (cSt):	37
	@ 100°C mm ² /sec (cSt):	7.3
Brookfield Viscosity	@ -40°C, mPa.s:	18000
Viscosity Index:		168
Pour Point °C:		-54
Flash Point °C:		215
Noack volatility, 200°C, % mass:		5
Foaming tendency/stability, ml	Stage I:	10/0
	Stage II:	30/0
	Stage III:	0/0
FZG Gear Test, A/8.3/90 failure load stage:		12

Revision Date: August 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk