



OPUS LUBRICANTS PRODUCT DATA

FAME 10W/40

Description

OPUS FAME 10W/40 is a semi-synthetic multigrade engine oil manufactured using high quality additives and base oils for fuel efficiency and superior performance for petrol and diesel engines of passenger cars and light commercial vehicles.

The additive technology coupled with Group 3 base fluids also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals.

Applications

FAME 10W/40 is suitable for normally aspirated and turbocharged diesel and petrol engines in passenger cars and light commercial vehicles.

Performance Levels

- API: SN/CF
- ACEA: A3/B4
- MB 229.3
- VW 502.00/505.00
- RN 0700/0710

Benefits

- Fuel economy, particularly when used in conjunction with FAME 75W/90 transmission oil.
- Suitable for a wide range of vehicles.
- Excellent high and low temperature stability.
- Excellent cold starting.
- Improved oil consumption and emissions.

Technical Data

SAE		10W/40
Specific Gravity	@ 15°C (typical)	0.870
Kinematic Viscosity	@ 100°C cSt	14.51
	@ 40°C cSt	100.00
Viscosity Index		152
Pour Point °C		-35
Flash Point COC (°C)		220
TBN (mg KOH/g)		10.2

Revision Date: January 2021

Ferguson & Menzies Ltd

312 Broomloan Road

GLASGOW

G51 2JW

Tel: 0141 445 3555

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk