



# OPUS LUBRICANTS PRODUCT DATA

## FAME 75W/90

### Description

**FAME 75W/90** is a high performance semi-synthetic automotive gear oil, it is manufactured with a combination of mineral oil and synthetic base stocks along with viscosity modifiers. It is suitable for use in high performance manual transmissions, spiral bevel axles, high load drive axles, hypoid axles and steering units.

### Performance Levels

- API: GL 5
- MIL-L-2105D
- ZF TE - ML 02
- ZF TE - ML 05

### Benefits

- For use in gear boxes and rear axles.
- Excellent syncromesh performance.
- Thermally very stable.
- Excellent cold starting.

### Typical Data

SAE		75W/90
Specific Gravity	@ 15°C	0.875
Kinematic Viscosity	@ 100°C cSt	15.80
Kinematic Viscosity	@ 40°C cSt	100.65
Viscosity Index		167
Pour Point (°C)		-48
Flash Point COC (°C)		179

Revision Date: September 2016

**Ferguson & Menzies Ltd**  
312 Broomloan Road  
GLASGOW  
G51 2JW

Tel: 0141 445 3555  
Fax: 0141 425 1079  
E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)  
Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)