



OPUS LUBRICANTS PRODUCT DATA

FAME-X 5W/30

Description

FAME X 5W/30 is a semi-synthetic engine oil manufactured using high quality additives and group 3 base oils, it is an extremely high performance long life diesel engine oil. The additive technology coupled with group 3 base oils also ensures a high level of component protection and cleanliness when operating in severe conditions with extended drain intervals.

Applications

FAME X 5W/30 has a wide range of applications including OEM's such as Volvo, Mercedes, DAF and MAN. It is also suitable for many buses, tractors and off highway applications.

Performance Levels

- API: CI4/SJ
- ACEA: E4 - E7
- Caterpillar: ECF2
- MAN: 3477
- Cummins: CES 20076/7/8
- Volvo: VDS-3
- Mercedes-Benz: 228.3
- Mack: EO-M +
- Renault: RLD/RLD-2
- Scania: LDF-2
- Ford WSS M2C – 913B

Benefits

- Extended intervals between oil changes.
- Improved performance under all conditions.
- Increased engine protection and low volatility, including all the latest Euro 4 – Euro 5 trucks and buses.

Typical Data

SAE		5W/30
Specific Gravity	@ 15°C	0.877
Kinematic Viscosity	@ 100°C cSt	9.7
	@ 40°C cSt	57.7
Viscosity Index		153
Pour Point °C		-27
Flash Point (COC °C)		215
TBN (mg KOH/gram)		10.5

Revision Date: April 2021