



OPUS LUBRICANTS PRODUCT DATA

HYDRAULIC 10W

Description

A high performance hydraulic oil designed to satisfy a wide range of heavy-duty hydraulic equipment requirements. This product is formulated from advanced base oils and specific additive system combined with inhibitors to reduce wear, oxidation, corrosion and rust. Opus Hydraulic 10W can be used in a wide range of on and off-highway hydraulic applications.

Performance Levels

- Denison: HF-1, HF-2, HF-O
- Vickers: 1-286-S, M-2950-S
- Cincinnati Milacron P-68, P-69, P-70
- DIN 51524, Part 2
- Ford M-6C32
- API: CD/SD

Benefits

- Excellent oxidation resistance and rust protection
- Good anti-wear protection
- Wide temperature range performance
- Anti-foam characteristics.

Typical Data

SAE GRADE		10W
Specific Gravity	@ 15°C	0.855
Kinematic Viscosity	@ 100°C cSt	5.6
	@ 40°C cSt	28.2
Viscosity Index		117
Pour Point (°C)		-36
Flash Point (°C)		200
TBN (mg KOH/gram)		10
Sulphated Ash (% weight)		1.4

Revision Date: May 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk