OPUS LUBRICANTS PRODUCT DATA

HYDRAULIC 10W

Description

A high performance hydraulic oil designed to satisfy a wide range of heavy-duty hydraulic equipment requirements. This product is formulated from advanced base oils and specific additive system combined with inhibitors to reduce wear, oxidation, corrosion and rust. Opus Hydraulic 10W can be used in a wide range of on and off-highway hydraulic applications.

Performance Levels

- Denison: HF-1, HF-2, HF-O
- Vickers: 1-286-S, M-2950-S
- Cincinnati Milacron P-68, P-69, P-70
- DIN 51524, Part 2
- Ford M-6C32
- API: CD/SD
- VDMA 24318

Benefits

- Excellent oxidation resistance and rust protection
- Good anti-wear protection
- Wide temperature range performance
- Anti-foam characteristics.

Typical Data

SAE GRADE		**10W**
Specific Gravity @ 15˚C		0.855
Kinematic Viscosity	@ 100˚C cSt	5.6
	@ 40˚C cSt	28.2
Viscosity Index		117
Pour Point (˚C)		-36
Flash Point (˚C)		200
TBN (mg KOH/gram)		10
Sulphated Ash (% weight)		1.4

Revision Date: November 2026

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW
Tel: 0141 445 3555 E-Mail: info@fergusonmenzies.co.uk Web: www.fergusonmenzies.co.uk