



# OPUS LUBRICANTS PRODUCT DATA

## MAX 10W/30 LOW SAPS

### Description

**OPUS MAX 10W/30** 'Low SAPS' is a heavy duty diesel engine oil with the latest API CK-4 and ACEA E11-22 specifications. Opus Max 10W/30 is formulated to meet the latest Euro V & Euro VI low emission requirements and is suitable for use in current low emission engines which employ advanced exhaust after treatment devices such as Diesel Particulate Filters (DPF), as well as Exhaust Gas Recirculation (EGR) and Selective Catalytic Reduction (SCR). It is formulated with a high performance additive system and is suitable for engines powered by both ultra low and low sulphur diesel providing superior protection and allowing extended oil drain servicing (subject to OEM recommendations and good operating practices).

### Applications

**OPUS MAX 10W/30** is designed to allow fleet operators to run their new vehicles to maximum drain intervals. Its primary application is for the latest low emission Euro V and Euro VI European trucks and buses, especially those requiring a Low SAPS lubricant.

### Performance Levels

- API: CK-4
- ACEA: E7, E9, E11-22
- MB: 228.31
- MAN M3775
- Volvo: VDS 4.5
- Renault: RLD4 / RLD-3
- Mack: EOS-4.5
- MTU Type 2.1
- Caterpillar ECF-3
- Deutz DQC III-18-LA
- Detroit Diesel: 93K222
- Cummins: CES 20086
- Ford: 171-F1
- JASO: DH-2

### Benefits

- Meets the current requirements of API CK-4
- Suitable for vehicles fitted with diesel particulate filters (DPF) as well as EGR and SCR
- Designed for both ultra low and low sulphur diesel (Low SAPS)
- Allows extended drain intervals between oil changes
- Enhanced soot control and dispersing capabilities
- Demonstrates good cold start up performance
- Minimises engine wear and oil consumption
- Fuel saving benefits
- Backward compatible to older models



### **Typical Data**

<b>SAE</b>		<b>10W/30</b>
Specific Gravity	@ 15°C	0.865
Kinematic Viscosity	@ 100°C cSt	11.60
	@ 40°C cSt	75.00
Viscosity Index		148
Sulphated Ash, wt %		1.0% max
Pour Point °C		-35
Flash Point (COC °C)		225
TBN (mg KOH/gram)		10.5

**Revision Date: March 2024**

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW  
Tel: 0141 445 3555      E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)      Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)