



OPUS LUBRICANTS PRODUCT DATA

PLUS 10W/30

Description

OPUS PLUS 10W/30 is an extremely high performance multigrade engine oil as indicated by the API classification of CH-4/SJ. It is manufactured from highly refined base oils quality additives producing high quality petrol and diesel engine oils.

They are eminently suitable for both turbo charged and naturally aspirated engines and are the perfect mixed fleet engine oils designed to give top performance in both petrol and diesel engines.

Performance Levels

- API: CH-4/SL
- ACEA: E5
- Mercedes Benz page 228.1
- MACK E0-K/2
- MAN 3275
- Allison C-4
- Volvo VDS-2
- MTU Cat 2

Advantages

- Mixed fleet advantages.
- Rationalisation of grades.
- Low temperature fluidity for easy starting: anti-wear, anti-oxidant and anti-corrosive properties.

Technical Data

SAE		10W/30
Specific Gravity	@ 15°C (typical)	0.868
Kinematic Viscosity	@ 100°C cSt	10.20
Kinematic Viscosity	@ 40°C cSt	64.0
Viscosity Index		148
Flash Point (COC °C)		198
Pour Point °C		-36
TBN (mg KOH-gram)		11.0

Revision Date: October 2017

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk