



OPUS LUBRICANTS PRODUCT DATA

ROCKDRILL OIL ISO 220

Description

Rockdrill Oil ISO 220 is an extreme pressure treated rock drill and pneumatic lubricant, designed for use in rock drills, jack hammers and other similar air operated tools.

On pneumatic tools, due to the expansion of air, the temperature may be considerably lower than ambient. Rockdrill Oil is formulated to be free flowing through airline lubricators and integral oilers under these conditions.

Benefits

- Excellent load carrying properties
- Superior corrosion protection
- Contains tackiness agents to help oil adhere to working parts

Typical Data

Appearance:		Amber liquid
Specific Gravity	@ 15.5°C	0.892
Kinematic Viscosity	@ 40.0°C (cSt)	225.00
Flash Point (COC°C)		220

Storage

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Revision Date: September 2016

Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555
Fax: 0141 425 1079
E-Mail: info@fergusonmenzies.co.uk
Web: www.fergusonmenzies.co.uk