



OPUS LUBRICANTS PRODUCT DATA

STOU 10W/30

Description

OPUS STOU 10W/30 is a multipurpose tractor oil manufactured from high quality base oils and additives meeting all the requirements of the mechanical components of the major manufacturers including 'wet' brakes, hydraulics, gears and transmissions.

The product is developed and tested for the most arduous duties of modern agricultural machinery with the additive package against the world's two major STOU specifications, Ford and Massey Ferguson, but is also acknowledged by other leading manufacturers.

Performance Levels

John Deere: J27 & J20C*
Massey Ferguson CMS M1139, M1144, M1145
Allison C4
API: GL4
Ford M2C 159 B
ZF TE-ML 06A, 06B, 06C, 06D, 07B
Caterpillar TO-2
API: CE, CF, CF-4, CG-4, SF
ACEA E2
MB: 228.1, 228.3
MAN 271
MIL-L-2104D

Benefits

- Multigrade and multifunctional.
- Rationalisation of grades.
- Additive package giving excellent oxidation and thermal stability.
- Excellent low-temperature flow characteristics, providing superior cold-start protection.
- Anti-'squawk'.
- Enhanced gear wear protection.
- Advanced hydraulic pump performance.



Physical Characteristics

SAE		10W/30
Specific Gravity	@ 15°C cSt	0.880
Kinematic Viscosity	@ 100°C cSt	10.7
	@ 40°C cSt	65.0
Viscosity Index		155
Pour Point (°C)		-45
Flash Point (COC°C)		200
TBN (mg KOH/gram)		10.7

Revision Date: October 2021

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW
Tel: 0141 445 3555 E-Mail: info@fergusonmenzies.co.uk Web: www.fergusonmenzies.co.uk