



OPUS LUBRICANTS PRODUCT DATA

SYNOPUS A.T.F. DEXRON VI

Description

SYNOPUS ATF Dexron VI is an automatic transmission fluid blended from synthetic base oils and a high performance additive package. It is a transmission fluid designed for use in modern automatic gearboxes, where GM Dexron VI is specified.

SYNOPUS ATF Dexron VI features many advantages over more traditional automatic transmission fluids such as improved shear stability, excellent wear control and extended fluid life. At low viscosity Synopus ATF Dexron VI provides performance for fuel efficient 6+ speed transmissions.

At high viscosity Synopus ATF Dexron VI provides added performance for older 3/4/5 speed transmissions.

Applications

SYNOPUS ATF Dexron VI is recommended for step type automatic transmissions and power steering units in cars, vans, trucks, buses and agricultural and industrial machines where the following specifications are required.

Performance Levels

- GM Dexron® VI/IIIH/IIIG/IID/ TASA
- JASO: 1A
- Allison C-4
- Caterpillar TO-2
- MB: 236.5
- Voith: 55.6335
- ZF: TE-ML09

Benefits

- Exceptional Low Temperature fluidity.
- Excellent resistance to oxidation and high thermal stability.
- Durability of friction characteristics and wear protection.
- Protection against rust and corrosion, and good seals compatibility.

Typical Data

Colour:		Red
Specific gravity	@ 15°C	0.850
Kinematic Viscosity	@ 100°C cSt	6.0
	@ 40°C cSt	28.00
Viscosity Index		168
Pour Point °C		-50
Flash Point °C		200

Revision Date: May 2017



Ferguson & Menzies Ltd
312 Broomloan Road
GLASGOW
G51 2JW

Tel: 0141 445 3555

Fax: 0141 425 1079

E-Mail: info@fergusonmenzies.co.uk

Web: www.fergusonmenzies.co.uk