



# OPUS LUBRICANTS PRODUCT DATA

## ULTRA LIFE 2

### Description

**OPUS Ultra Life 2** is a super High-Performance Calcium Sulfonate Grease with exceptional load carrying capacity designed to provide extended relubrication intervals in a wide range of applications including extreme working conditions. Opus Ultra Life 2 is suitable for use in all types of anti-friction, plain bearings and sliding surfaces.

### Benefits

- Extends lubrication intervals ensuring maximum cost savings in grease consumption
- Highly water resistance and corrosion protection.
- Excellent EP performance provides protection against premature wear
- Highly versatile grease with a wide temperature range.

### Application

Ultra Life 2 can be applied by hand, or by using a standard grease gun or via a central lubricating system designed for and capable of pumping an NLGI No.2 grease.

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.



### Typical Physical Properties

Appearance -	Brown adhesive Smooth Grease
NLGI Classification -	2
Thickener -	Calcium Sulphonate Complex
Base fluid -	Mineral oil
Base Oil Viscosity @40°C (IP 71) -	460 cSt
Dropping point (ASTM D2265) -	>280°C
Water washout (IP 215, ASTM D1264) @ 38°C -	<1%
Dynamic corrosion resistance (IP 220) -	0:0
Copper corrosion (IP 112) -	1a
Shell Four Ball (IP 239)	
Weld load -	800kgs
Mean Hertz Load -	110kg
Timken OK load (IP236) -	60 lbs
Operating temperature range -	-30°C to +150°C short periods 200°C

Revision Date: April 2026

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW

Tel: 0141 445 3555

E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)

Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)