



# OPUS LUBRICANTS PRODUCT DATA

## FAME HT PLUS 10W-30

### Description

**Opus Fame HT Plus 10-30** is a multifunctional Semi-Synthetic transmission and hydraulic fluid for tractors and plant. Manufactured from Group III base fluids, Fame HT Plus is suitable for use in traditional gearboxes, CVT, Power-Shift and Shuttle-Shift gearboxes, rear transmissions with wet brakes, side final drives, wheel final drives, differentials, hydraulic hoists, drive pulley, mechanical and hydrostatic drives, and power steering units.

### Performance Levels

- John Deere J20D
- Volvo WB 102 (97304), WB 101 (97303),
- API GL-4
- Massey Ferguson M1145, M1143, M1141, M1135,
- Case New Holland MAT 3540, 3526, 3525, 3505,
- Case MS 1206, 1207, 1209, 1210,
- New Holland NH 420A, 410B,
- ZF TE-ML 03E, 05F, 06K, 17E,
- Kubota Super UDT, UDT,
- Valtra G2-08,
- Allison C-4,
- Caterpillar TO-2,
- FORD M2C134-D, M2C86-B,
- Komatsu AXO80

### Benefits

- Excellent anti-squawk properties.
- Suitable for nearly all hydraulic, transmission and differential systems.
- Excellent thermal and oxidation stability.

### Typical Data

SAE		10W-30
Specific Gravity	@ 15 °C	0.866
Kinematic Viscosity	@ 100 °C cSt	11.50
	@ 40 °C cSt	66.80
Viscosity Index		145
Pour Point °C		-42°C

Revision Date: June 2025

Ferguson & Menzies Ltd, 312 Broomloan Road, GLASGOW, G51 2JW

Tel: 0141 445 3555

E-Mail: [info@fergusonmenzies.co.uk](mailto:info@fergusonmenzies.co.uk)

Web: [www.fergusonmenzies.co.uk](http://www.fergusonmenzies.co.uk)